

Product Specifications

Jumbo Display Wall Mount Thermo-Hygrometer

Temperature Range	Internal Sensor: 14°F to 122°F (-10°C to 50°C) External Probe: -58°F to 158°F (-50°C to 70°C)
Humidity Range	Internal: 10% to 99%
Operating Range	14°F to 122°F (-10°C to 50°C)
Humidity Accuracy (Internal)	±5% R.H. from 40% to 70% R.H. at 77°F~86°F (25°C~30°C)
Temperature Accuracy (Internal & External)	±1.8°F (1°C) from 32°F to 104°F (0°C to 40°C)
External Temperature Sensor	Cable length: 6.56ft/2m Probe: 20mm L x 4mm D
Resolution	R.H.1%, temperature 0.1°F/°C
Temperature Update on LCD	20 seconds
Display Auto Update	Internal Temp/Time & External Temp/Date switches every 5 seconds
Display Window Size	3.15in W x 2.36in H (80mm W x 60mm H)
Character Height within Display	1.02in (26mm) - Temperature & Humidity 0.87in (22mm) - Date & Time
Product Size	3.74in W x 4.02in H x 0.75 in D (95mm W x 102mm H x 19mm D)
Weight	4.18oz (118.4g)
Body Casing	Polycarbonate and ABS plastic
Sensor Type	Temperature: thermistor Humidity: electronic resistive
Battery	One 1.5v AAA Zinc-Carbon
Certification/Calibration	CE mark, NIST traceable calibration certificate



Model 13309

- Serial number and calibration certificate traceable to NIST standards
- Internal temperature and humidity sensors
- External temperature probe
- Probe holder with self-adhesive backing
- °C/°F selectable
- Jumbo display for temperature, humidity, time and date
- Min/Max memory - lowest and highest readings stored for instant recall
- Alarm clock and hourly chime

DeltaTrak manufactures and operates under an ISO 9001:2015 registered quality management system



Representative



特旺通科藝私營有限公司
THERMOTRON-CE TECHNOLOGY PTE LTD

10 Bukit Batok Crescent #05-03 The Spire, Singapore 658079
T (65)6896 1586 | WA (65)9829 4363 | www.thermotron-ce.com.sg
sales@thermotron-ce.com.sg | mailbox@thermotron-ce.com.sg